

## Fabco TC-137 Transfer Case Parts Manual


Pro Gear Fabco TC-137 Transfer Case Parts Manual to assist in identifying your Meritor / Fabco unit.


If you need any assistance identifying the correct transfer case unit for your truck and equipment, contact your Meritor / Fabco replacement part specialists at Pro Gear and Transmission.


Pro Gear Transmission has same day shipping and 1000's of products in stock and ready to ship internationally for your next project.

For parts or service contact the Meritor / Fabco specialists at Pro Gear & Transmission, Inc.

1 (877) 776-4600 (407) 872-1901 parts@eprogear.com







## NOTES:

E

D

С

\_\_\_\_\_

B

A

8


1 SELECT SHIMS, ITEM 68, TO OBTAIN .003T TO .003L END FLOAT ON THE UPPER SHAFT. 2 SELECT SHIMS, ITEM 69, TO OBTAIN .003T TO .003L END FLOAT ON THE LOWER OUTPUT SHAFT. 3 SELECT SHIMS, ITEM 70, TO OBTAIN .003T TO .003L END FLOAT ON THE INTERMEDIATE SHAFT. 4 SELECT SHIMS, ITEM 73, TO OBTAIN .003T TO .003L END FLOAT ON THE LOWER FRONT OUTPUT SHAFT.

Pro Gear and Transmission • 906 W. Gove St. Orlando, FL 32805 • 1 (877) 776-4600 / (407) 872-1901 • parts@eprogear.com






ſ	Material - Heat Treatment - Finish		
L			Remov
L		Unless otherwise specified, all tolerances are as follosw:	Part
	The design and technical information apperring on this drawing is the prop- erty of Fabco Automotive Corp., and is disclosed in confidence. It is not to be copied, reproduced, revealed to, or appropriated by others, either in whole, or in part, without the expressed wr itten consent of Fabco Automotive Corp.	✓  RUNOUT  .005 TOTAL  DECIMALS:    ◎  CONCENTRICITY  .005 TOTAL  .X ± .060    ✔  CYLINDRICITY  .003  .XX ± .030    //  PARALLELISM  .005 ⑤  .XXX ± .010    Ø  FLATNESS  .005 ⑤  FRACTIONS: ± 1/32    ♦  POSITION  .020 ⑤  DRILLED HOLES:    ○  ROUNDNESS  .003 002 ± .008    ¬  STRAIGHTNESS  .005 ⑤  SURFACE FINISH:	873-0126
	This drwaing shows final dimensions. Machining must allow for subsequent processing, plating, heat treatment, etc.	➡  SYMMETRY  .060  250 RMS    ∠  ANGULARITY  .030 S  XXXX  BASIC, EXACT    ⊥  PERPENDICULARITY  .005 S  DIMENSION    All tolerance interpretations per ANSI Y14.5	Engr. Approval Prod. Approval Revision Date
	3		2











Material - Heat Treatment - Finish		Ren
<b>-</b>	Unless otherwise specified, all tolerances are as follosw:	Part
The design and technical information apperring on this drawing is the prop- erty of Fabco Automotive Corp., and is disclosed in confidence. It is not to be copied, reproduced, revealed to, or appropriated by others, either in whole, or in part, without the expressed wr itten consent of Fabco Automotive Corp.	<i>P</i> RUNOUT        .005 TOTAL     DECIMALS:            © CONCENTRICITY        .005 TOTAL     .X ± .060 <i>P</i> CYLINDRICITY        .003     .XX ± .030 <i>P</i> PARALLELISM        .005 ⑤     .XX ± .010 <i>P</i> FLATNESS        .005 ⑤     FRACTIONS: ± <b>Φ</b> POSITION        .020 ⑤     DRILLED HOLESS <i>Q</i> ROUNDNESS        .003    002 +.008	1/32 Drawn I TRAN
This drwaing shows final dimensions. Machining must allow for subsequent processing, plating, heat treatment, etc.	→  STRAIGHTNESS  .003 002 + .008    →  STRAIGHTNESS  .005  SURFACE FINIS    =  SYMMETRY  .060  250 RMS    ∠  ANGULARITY  .030  S  XXXX    ↓  PERPENDICULARITY  .005  S  DIMENSION	H: ACT
	All tolerance interpretations per ANSI Y14.5	Revision Date

